

# TECHNICAL DATA SHEET

**PRODUCT CODE(S):**

Q-0410

**PRODUCT DESCRIPTION:**

W/B INSIDE TIRE LUBE

**PHYSICAL PROPERTIES:**

COLOR:	LIGHT BROWN	
TYPE:	WATER-BASED	
VISCOSITY:	60-70 KU	
WEIGHT PER GALLON:	8.87	lbs/gal ± 0.30 lbs.
	1.06	g/ml ± 0.04 g/ml
SPECIFIC GRAVITY (ASTM D 1475-90):	1.065	± 0.04
GLOSS @ 60°:	N/A	
pH:	8-10	
FLASH POINT:	> 214 °F	101.1 °C
SOLIDS:	21.6	% by weight
	16.22	% by volume
THEORETICAL COVERAGE:	260.17	ft <sup>2</sup> / gal @ 1.0 mil dry
	6.38	m <sup>2</sup> /l @ 25.4 μ
VOC:	0.30	lb(s)/gal ( 36.0 g/l)
VOC (U.S.):	0.30	lb(s)/gal ( 36.0 g/l)

**APPLICATION:**

METHOD:	CONVENTIONAL SPRAY
CURE METHOD:	AIR DRY
REDUCTION:	USE AS SUPPLIED
CLEAN UP:	WATER
RECOMMENDED EQUIPMENT:	

**SUBSTRATE:**

TYPE:	UNCURED RUBBER COMPOUNDS
PREPARATION:	CLEAN, DRY SURFACE, FREE OF OIL OR CONTAMINANTS.

**HANDLING & STORAGE:**

SHELF LIFE:	12 MONTHS
FREEZE CAUTION:	PROTECT FROM FREEZING
RECOMMENDED STORAGE:	STORE IN COOL, DRY AREA.

**ADDITIONAL GUIDELINES:**

SHAKE WELL BEFORE USE.

## A focused partner in advanced coating, chemical & manufacturing solutions...

Founded in 1878, APV Engineered Coatings custom engineers and manufactures industrial coatings and advanced chemical products out its state-of-the-art facility in Akron, Ohio. APV is a partner for some of the world's top producing manufacturers due to our expertise in chemical composition, the commercialization of advanced materials, and large-scale production with acute quality control. Our innovative solutions have been integrated into a variety of industries for unique applications.

At APV, clients work with knowledgeable and personable staff who are focused on delivering optimum solutions in an unprecedented timeframe. APV thrives by recognizing the importance of our clients' success, which have proved to create long-standing partnerships.

**APV Engineered Coatings, Inc.**1390 Firestone Parkway  
Akron, Ohio 44301 USA  
800.772.3452sales@apvcoatings.com  
www.apvcoatings.com

rev. date: 02/21/2020

The information and data given herein are based upon tests and reports considered reliable and are believed to be accurate. However, due to varied application and handling methods, no guarantee of duplicate performance, expressed or implied, is made.