

TECHNICAL DATA SHEET

**PRODUCT CODE(S):**

A-1339

PRODUCT DESCRIPTION:

White Aeroprte

PHYSICAL PROPERTIES:

COLOR:	White
TYPE:	Solvent Base
VISCOSITY:	17-19 #2 Zahn Cup
WEIGHT PER GALLON:	8.57 lbs/gal ± 0.30 lbs.
	1.03 g/ml ± 0.04 g/ml
SPECIFIC GRAVITY (ASTM D 1475-90):	1.030 ± .04
GLOSS @ 60°:	45-55
pH:	N/A
FLASH POINT:	24 °F -4.4 °C
SOLIDS:	27.5 % by weight
	11.7 % by volume
THEORETICAL COVERAGE:	187.67 ft ² / gal @ 1.0 mil dry
	4.60 m ² /l @ 25.4 μ
VOC:	6.22 lb(s)/gal (745.9 g/l)
VOC (U.S.):	6.22 lb(s)/gal (745.9 g/l)

APPLICATION:

RECOMMENDED FILM THICKNESS:	7.00 mil (wet) 183.13 g/m ²
	0.82 mil (dry) 50.36 g/m ²
COVERAGE:	229.14 ft ² /gal @ 0.82 mil (dry)
METHOD:	Spray
CURE METHOD:	Air Dry
REDUCTION:	63% paint 35% acetone 3% PM acetate
CLEAN UP:	acetone or other suitable solvent
RECOMMENDED EQUIPMENT:	Conventional Air Spray

SUBSTRATE:

TYPE:	Aluminum
PREPARATION:	Clean, Dry, and Free From Oil

HANDLING & STORAGE:

SHELF LIFE:	1 Year aerosol 2 Years Liquid
FREEZE CAUTION:	None
RECOMMENDED STORAGE:	Cool, Dry, Well Ventilated Area

ADDITIONAL GUIDELINES:

Mix Well Before Using. Close container after each Use.

A focused partner in advanced coating, chemical & manufacturing solutions...

Founded in 1878, APV Engineered Coatings custom engineers and manufactures industrial coatings and advanced chemical products out its state-of-the-art facility in Akron, Ohio. APV is a partner for some of the world's top producing manufacturers due to our expertise in chemical composition, the commercialization of advanced materials, and large-scale production with acute quality control. Our innovative solutions have been integrated into a variety of industries for unique applications.

At APV, clients work with knowledgeable and personable staff who are focused on delivering optimum solutions in an unprecedented timeframe. APV thrives by recognizing the importance of our clients' success, which have proved to create long-standing partnerships.



APV Engineered Coatings, Inc.
1390 Firestone Parkway
Akron, Ohio 44301 USA
800.772.3452
sales@apvcoatings.com
www.apvcoatings.com