

TECHNICAL DATA SHEET

**PRODUCT CODE(S):**

P-9562

PRODUCT DESCRIPTION:

RUBBER REPAIR PAINT

PHYSICAL PROPERTIES:

COLOR:	BLACK
TYPE:	WATER BASED
VISCOSITY:	900-1100 CPS
WEIGHT PER GALLON:	8.64 lbs/gal ± 0.30 lbs.
	1.04 g/ml ± 0.04 g/ml
SPECIFIC GRAVITY (ASTM D 1475-90):	1.041 ±
GLOSS @ 60°:	2-6
pH:	8.3-9.1
FLASH POINT:	212 °F 100.0 °C
SOLIDS:	14.13 % by weight
	10.8 % by volume
THEORETICAL COVERAGE:	173.23 ft ² / gal @ 1.0 mil dry
	4.25 m ² /l @ 25.4 μ
VOC (WET):	0.08 lb(s)/gal (9.6 g/l)
VOC (DRY):	0.64 lb(s)/gal (76.7 g/l)

APPLICATION:

RECOMMENDED FILM THICKNESS:	2.00 mil (wet) 52.88 g/m ²
	0.22 mil (dry) 7.47 g/m ²
COVERAGE:	802.00 ft ² /gal @ 0.22 mil (dry)
METHOD:	SPRAY OR SPONGE MITT
CURE METHOD:	
REDUCTION:	NONE REQUIRED, USE AS SUPPLIED
CLEAN UP:	WATER OR L-400
RECOMMENDED EQUIPMENT:	CONVENTIONAL SPRAY EQUIPMENT

SUBSTRATE:

TYPE: CURED RUBBER COMPOUND

PREPARATION: CLEAN DRY SURFACE, FREE OF OIL AND LUBRICANTS

HANDLING & STORAGE:

SHELF LIFE:	12 MONTHS UNOPENED
FREEZE CAUTION:	Protect from freezing
RECOMMENDED STORAGE:	COOL DRY LOCATION

ADDITIONAL GUIDELINES:

Mix well before using. Close container after use. Light coat necessary for good coverage,

A focused partner in advanced coating, chemical & manufacturing solutions...

Founded in 1878, APV Engineered Coatings custom engineers and manufactures industrial coatings and advanced chemical products out its state-of-the-art facility in Akron, Ohio. APV is a partner for some of the world's top producing manufacturers due to our expertise in chemical composition, the commercialization of advanced materials, and large-scale production with acute quality control. Our innovative solutions have been integrated into a variety of industries for unique applications.

At APV, clients work with knowledgeable and personable staff who are focused on delivering optimum solutions in an unprecedented timeframe. APV thrives by recognizing the importance of our clients' success, which have proved to create long-standing partnerships.



APV Engineered Coatings, Inc.
1390 Firestone Parkway
Akron, Ohio 44301 USA
800.772.3452
sales@apvcoatings.com
www.apvcoatings.com